

## RELEASE LIQUIDS

Tygavac has a range of release liquids for use with composite and metal tooling to provide release of cured composite parts from mould tools.

Product Reference	Description	Maximum Use °C
RA 20	Water based liquid wax	177°C
RA 30	Release All Safelease 30 Water based PTFE liquid	232°C
SP 441 & SP 701	Non-silicone semi permanent aliphatic hydrocarbon release agent	250°C
TS 151	Tool sealer for new and freshly cleaned tools	250°C



### SAFELEASE ADVANTAGES:

- No Silicone Transfer
- No Corrosion On Metal Tools
- Multiple Cycles With One Application
- Maximum Use Temperature 450 °F 232 °C
- Does Not Attract Moisture Or Retain Moisture
- Works On Composite And Metal Tools Without Sealer
- One Release Agent That Releases From All Resin Systems



MORE THAN A MANUFACTURER... **A TECHNICAL PARTNER**

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and / or completeness are not guaranteed. The user shall determine the suitability of the product for his particular purpose and shall assume all risk and liability in connection therewith. All products are sold subject to Tygavac Advanced Materials standard Conditions of Sale.

Tygavac™ is a registered Trade Mark